

SB 222 (TYPE-2T / C2TE)

Premium adhesive for indoor and outdoor application



PRODUCT INTRODUCTION

SB 222 IS High polymer modified grey cement based single component adhesive for vitrified tiles on indoor and outdoor wall/floor surface. It provides exceptional adhesion and flexibility ensuring a long lasting and durable finish.

RECOMMENDED APPLICATION

- Indoor and outdoor wall and floor ceramic and vitrified tiles fixing
- Residential And Light Commercial Floors
- Cement plaster, cement screed, concrete surface.
- suitable for wet areas in indoor application
- Apply only on dry and dust free surfaces.



TECHNICAL SPECIFICATION (AS PER IS 15477)

PROPERTY	TYPICAL VALUE
Appearance	Grey powder
Tensile Adhesion Strength dry condition (after 28 days)	1 N/MM ²
Tensile Adhesion Strength wet condition (after 28 days)	1 N/MM ²
Tensile Adhesion Strength heat condition (after 28 days)	1 N/MM ²
Shear Adhesion Strength dry condition (after 28 days)	1.25 N/MM ²
Open time	20 MINUTES
Slip Resistance	< 0.5 MM
Pot Life	45 MINUTES
Grouting Time	After 24 hours
Water Mixing Ratio	22 to 24 % by weight of powder
Shelf life	12 months from the date of manufacture
Pack size	20 kg