

SB 333 (TYPE-3T / C2TE)

Premium adhesive for heavy duty and high traffic indoor and outdoor application



PRODUCT DESCRIPTION

SB 333 IS High polymer modified grey cement based single component adhesive formulated for large format tiles, heavy stone, high traffic areas. It is also suitable for tile on tile application.

RECOMMENDED APPLICATION

- Indoor and outdoor large format vitrified tiles and glass mosaic
- Natural stone, marble, granites (framing application)
- Cement plaster, cement screed, concrete surface.
- suitable for wet areas in indoor and outdoor application
- Apply only on dry and dust free surfaces.



TECHNICAL SPECIFICATION (AS PER IS 15477)

PROPERTY	TYPICAL VALUE
Appearance	Grey powder
Tensile Adhesion Strength dry condition (after 28 days)	1.5 N/MM2
Tensile Adhesion Strength wet condition (after 28 days)	1 N/MM2
Shear Adhesion Strength dry condition (after 28 days)	1.5 N/MM2
Shear Adhesion Strength wet condition (after 28 days)	1 N/MM2
Open time	20 MINUTES
Slip Resistance	< 0.5 MM
Pot Life	45 MINUTES
Grouting Time	After 24 hours
Water Mixing Ratio	23 to 25 % by weight of powder
Shelf life	12 months from the date of manufacture
Pack size	20 kg