

SB BLOCK BOND

High performance ready to use mortar for AAC Blocks.

PRODUCT INTRODUCTION

Dufix Block Bond is a high polymer modified cement based thin jointing material designed for laying AAC Blocks, It ensure superior adhesion workability and durability in masonry construction.

RECOMMENDED APPLICATION

- AAC Block jointing works
- Apply the mortar in a thin layer (3-5mm) using a notched trowel

PRECAUTIONS

- Ensure Block Surface Are Clean, Dust Free And Wet Condition While Application.
- Remove Loose Particals, Oil, Grease, Or Curing Compounds From Block Surface.
- Use Clean Water Potable For Mixing.
- Always Add Powder into Water, not The Other way Around.
- Avoid Use During Heavy Rain or Freezing Conditions.
- Use The Mortar Within 40-50 Minutes Of Mixing.

TECHNICAL SPECIFICATION (AS PER IS 15477)

PROPERTY	TYPICAL VALUE
Appearance	Grey powder
Compressive Strength (After 28 days)	6 N/MM2
Tensile Strength (After 28 days)	0.8 N/MM2
Pot Life	1 hour (27.c)
Water Mixing Ratio	25 % by weight of powder
Shelf Life	12 months from the date of manufacture
Pack Size	40 kg

